



VIVID FX

MSDS No.:6200 Series

MSDS Preparation Date: January 3, 2007

Page 1 of 15

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name : **VIVID FX**
 Vivid FX Bright White (No. 6250)
 Vivid FX Orange Sunset (No.6252)
 Vivid FX Magenta (No.6256)
 Vivid FX Violet (No.6257)
 Vivid FX Deep Blue (No.6258)
 Vivid FX Brilliant Blue (No. 6259)
 Vivid FX Aquamarine (No.6260)
 Vivid FX Deep Green (No.6262)

Product Use : Paint
Chemical Family : Mixture.

Supplier's name and address:

Rosco Laboratories Inc.

52 Harbor View Avenue
 Stamford, CT, United States
 06902

24 Hr. Emergency Tel # : (800) 424-9300

HMIS Rating : *- Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: 1 *Flammability:* 0 *Reactivity:* 0

WHMIS Classes:



TOXIC

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

| <u>Ingredients</u> | <u>CAS #</u> | <u>% (weight)</u> | <u>ACGIH TLV</u> | | <u>OSHA PEL</u> | |
|--------------------------|--------------|-------------------|------------------|-------------|-----------------|-------------|
| | | | <u>TWA</u> | <u>STEL</u> | <u>PEL</u> | <u>STEL</u> |
| No hazardous ingredients | N/A-v | N/Av | N/Av | N/Av | N/Av | N/Av |

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Liquid in multiple colors. No special hazards exist with this product. As with any chemical substance, caution and care will prevent unnecessary accidents and safety problems. Read instructions on label before use.

POTENTIAL HEALTH EFFECTS

Target organs : None reported by the manufacturer.

Routes of exposure : *Inhalation:* YES *Skin Absorption:* YES *Skin & Eyes:*YES *Ingestion:* YES

Potential acute health effects :

Eyes: Causes eye irritation. May cause conjunctivitis, irritation, and inflammation of mucous membranes. May cause burning sensation, redness and tearing (watering). Possible severe irritation.

Skin: Irritating to skin. Possible irritation, defatting or dermatitis (rash). Components of the product may be absorbed into the body through the skin. May cause central nervous system depression.



VIVID FX

MSDS No.:6200 Series

MSDS Preparation Date: January 3, 2007

Page 2 of 15

Inhalation: Can cause irritation of the respiratory tract. Prolonged exposure to vapors may be harmful to health. If higher concentrations are inhaled, additional symptoms may include coughing, shortness of breath, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. May cause mucous membrane irritation. Other adverse effects : Asphyxia. Severe lung irritation or lung damage, loss of appetite. Sanding and grinding dusts may be harmful if inhaled. Contains particles which may cause lung damage if inhaled in large quantities.

Ingestion: Lung aspiration hazard. This product may be aspirated (inhaled) into the lungs during ingestion. May cause lung inflammation. May cause mucous membrane irritation. Ingestion may cause symptoms similar to inhalation. May cause gastrointestinal irritation. Gastrointestinal irritation may include abdominal pain, nausea, diarrhea and vomiting. Other adverse effects : intoxication.

Potential chronic health effects

: Prolonged skin contact may defat the skin and produce dermatitis. Harmful by skin absorption. May cause central nervous system depression. Prolonged inhalation of vapors may cause lung damage, including chronic bronchitis.

Medical conditions aggravated by overexposure

: None expected, when used as intended.

Additional health hazards

: None reported by the manufacturer.

Potential environmental effects

: None reported by the manufacturer.

SECTION 4 - FIRST AID MEASURES

- Inhalation** : If breathed in, move person into fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.
- Skin contact** : Flush with plenty of water. Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If irritation persists, seek prompt medical attention.
- Eye contact** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If irritation persists, seek prompt medical attention.
- Ingestion** : Call a physician or Poison Control Centre immediately. Do NOT induce vomiting. Guard against aspiration into lungs by having the individual turn on their left side.
- Notes For Physician** : Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

: Not flammable under normal conditions of handling. This product will not burn, due to its water content.

Flammability classification (OSHA 29 CFR 1910.1200)

: OSHA Combustible Liquid IIIB.

Flash point

: Not applicable.

Flash point Method

: Not applicable.

Auto-ignition temperature : Not available.

Lower flammable limit (% by vol.)

: Not applicable.

Upper flammable limit (% by vol.)

: Not applicable.

Suitable extinguishing media

: Dry chemical, foam, carbon dioxide and water fog.

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

Special fire-fighting procedures/equipment

: Firefighters should wear an approved full-face, self-contained breathing apparatus (SCBA) and impervious clothing. Water may be ineffective on fire, but may be helpful in cooling unburned containers. Do not use a solid water stream as it may scatter and spread fire. If water is used, fog nozzles are preferable.

Hazardous combustion products

: Oxides of carbon, nitrogen, and sulphur. Oxygen. Acrid fumes, toxic gases.

Oxidizing properties

: None reported by the manufacturer.



SECTION 6 - ACCIDENTAL RELEASE MEASURES

- Personal precautions** : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Avoid breathing vapors. Wear resistant clothing and boots.
- Environmental precautions** : Prevent product from entering drains, sewers, waterways and soil.
- Spill response/cleanup** : Eliminate all ignition sources if safe to do so. Ventilate area of release. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13).
- Containment** : Should not be released into the environment. Recover free liquid or cover with inert absorbent material and place into appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

- Safe Handling procedures** : Use with adequate ventilation. Avoid breathing vapor or mist. Avoid contact with skin and eyes. Wash hands thoroughly after using this product, and before eating, drinking or smoking. Avoid breathing of dust created by cutting, sanding, or grinding. Sanding and grinding dusts may be harmful if inhaled. Do not re-use empty containers. Do not puncture container. Keep in properly labeled containers. Wear suitable protective equipment. Do not ingest. Keep out of direct sunlight.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Do not freeze. Keep container tightly closed when not in use. Store in upright position only. Keep out of the reach of children. Empty product containers may contain hazardous product residue. Store out of direct sunlight. Do not store near acids or acid-based products. Do not store in metal containers. When metal sprayers are used, they should be thoroughly cleaned immediately after use, including nozzles and accessories. Avoid use of metal buckets or paint containers when possible.
- Incompatible materials** : Oxidizing agents. Acids and bases. Aluminum. Ammonium salts. Other: magnesium, chlorinated rubber.
- Special packaging materials** : Liquid-proof glass, plastic or non-corrodible metal containers are recommended.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Ventilation and engineering measures** : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Use explosion-proof equipment. Discharge exhaust only in area away from ignition sources.
- Respiratory protection** : Use NIOSH/MSHA approved full-face respirator with an organic vapor cartridge if the recommended exposure limit is exceeded. In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.
- Skin protection** : Gloves impervious to the material are recommended.
- Eye / face protection** : Safety glasses with side-shields or chemical splash goggles.
- Other protective equipment** : Emergency showers and eyewash facilities should be nearby. Depending on conditions of use, safety shoes and additional protective clothing may also be necessary.
- General hygiene considerations** : Wash hands thoroughly after using this product, and before eating, drinking or smoking. Wash hands before breaks and at the end of workday.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|-------------------------------|------------------|--|------------------------------|
| Physical state | : Liquid. | Appearance | : Liquid in multiple colors. |
| Odor | : Not available. | Odor threshold | : Not available. |
| pH | : Not available. | | |
| Boiling point | : 100 °C | Specific gravity | : 1.0 - 1.1 |
| Melting/Freezing point | : Not available. | Coefficient of water/oil distribution | |



VIVID FX

MSDS No.:6200 Series

MSDS Preparation Date: January 3, 2007

Page 4 of 15

Vapor pressure (mmHg @ 20° C / 68° F) : Not available.
 : 0.6 - 29.3
 1.0 (No. 6258)

Solubility in water : Soluble

Vapor density (Air = 1) : Heavier than air.

Evaporation rate (n-Butyl acetate = 1)
 : Slower than n-butyl acetate

Volatile organic Compounds (VOC's) (lbs/gal;g/l) : 71.96
 : 0.72/86.8 (No.6250)
 0.41/49.20 (No.6252)
 0.44/52.43 (No.6256)
 0.46/55.67 (No.6257)
 0.59/70.98 (No.6258)
 0.40/48.14 (No.6259)
 0.41/49.50
 (No.6260/6262)

Volatiles (% by weight) : 54.4 (No. 6262)

Viscosity : Not available.

Special Remarks On Fire Hazards
 : Not flammable under normal conditions of use. This product will not burn, due to its water content. May spatter if the temperature exceeds the boiling point. Vapors may irritate eyes. May irritate skin.

SECTION 10 - REACTIVITY AND STABILITY DATA

Stability and reactivity : Stable under normal conditions.

Hazardous polymerization : Will not occur.

Conditions to avoid : High temperatures. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Oxidizing agents. Do not freeze.

Materials To Avoid And Incompatibility
 : See Section 7 (Handling and Storage) section for further details.

Hazardous decomposition products
 : See hazardous combustion products.

SECTION 11 - TOXICOLOGICAL INFORMATION

| <u>Ingredients</u> | <u>LC₅₀(4hr)</u> <u>inh, rat</u> | <u>LD₅₀</u> | |
|--------------------------|--|------------------------|---------------|
| | | <u>oral</u> | <u>dermal</u> |
| No hazardous ingredients | N/Av | N/Av | N/Av |

Toxicological data : Low order of toxicity for normal industrial handling.

Carcinogenic status : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects : Not expected to have other reproductive effects.

Teratogenicity : Not expected to be a teratogen.

Mutagenicity : Not expected to be mutagenic in humans.

Reproductive Effects : Not expected to have other reproductive effects.

Irritancy : Eyes, skin, respiratory system and digestive system.

Sensitization to material : Not expected to be a sensitizer.

Synergistic materials : None reported by the manufacturer.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental effects : None known or reported by the manufacturer.

Important environmental characteristics
 : None known or reported by the manufacturer.

Ecotoxicological : No data is available on the product itself.



VIVID FX

MSDS No.:6200 Series

MSDS Preparation Date: January 3, 2007

Page 5 of 15

SECTION 13 - DISPOSAL CONSIDERATIONS

- Handling for Disposal** : See Section 7 (Handling and Storage) section for further details.
Methods of Disposal : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules. Do not puncture or incinerate. Contact waste disposal services.

SECTION 14 - TRANSPORTATION INFORMATION

| Regulatory Information | UN Number | Shipping Name | Class | Packing Group | Label |
|---|-----------|----------------|---------------|---------------|-------|
| TDG | None | Not regulated. | Not regulated | -None- | |
| TDG Additional information | None. | | | | |
| 49CFR/DOT | None | Not regulated. | Not regulated | -None- | |
| 49CFR/DOT Additional information | None. | | | | |
| ICAO/IATA | None | Not regulated. | Not regulated | -None- | |
| ICAO/IATA Additional information | None. | | | | |
| IMDG | None | Not regulated. | Not regulated | -None- | |
| IMDG Additional information | None. | | | | |

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

All ingredients are listed on the TSCA Inventory, or are exempted materials.
 SARA Section 313: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical Constituents above de minimus concentrations.

US State Right to Know Laws:

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

Canadian Regulations:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian WHMIS Classification: D2B.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16 - OTHER INFORMATION



VIVID FX

MSDS No.:6200 Series

MSDS Preparation Date: January 3, 2007

Page 6 of 15

Legend : ACGIH: American Conference of Governmental Industrial Hygienists
IARC: International Agency for Research on Cancer
N/Ap: not applicable
N/Av: not available
NIOSH: National Institute of Occupational Safety and Health
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration

References : Information obtained from sources including original supplier's Material Safety Data Sheet, and references including RTECS and CCOHS Cheminfo.

| | |
|--|--|
| <p>Prepared for: Rosco Laboratories Inc. 52 Harbor View Avenue Stamford, CT, USA, 06902 Phone: (203) 708 8900 http://http://www.rosco.com/</p> | |
| <p>Prepared by: ICC The Compliance Center Inc. Canada: 1-888-977-4834 USA: 1-888-442-9628 http://www.thecompliancecenter.com</p> | |

DISCLAIMER OF LIABILITY

Every effort has been made to ensure that the safety information on this sheet is accurate, but because Rosco Laboratories, Inc. has no control over the conditions under which the product will be used, liability is limited exclusively to replacement or refund of the purchase price of this product. Except as stated herein, there are no express or implied warranties, including implied warranties of merchantability or fitness for a particular purpose. Rosco Laboratories, Inc. assumes no liability for injury or incidental or consequential damages arising out of storage, handling or use of this product.

Preparation Date: January 3, 2007



VIVID FX

MSDS No.:6251, 6253, 6254, 6255, 6261

MSDS Preparation Date: January 3, 2007

Page 7 of 15

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name : **VIVID FX**
Vivid FX Lemon Yellow (No.6251)
Vivid FX Scarlet Red (No.6254)
Vivid FX Orange (No.6253)
Vivid FX Hot Pink (No.6255)
Vivid FX Electric Green (No.6261)

Product Use : Paint

Chemical Family : Mixture

Supplier's name and address:

Rosco Laboratories Inc.

52 Harbor View Avenue
Stamford, CT, United States
06902

24 Hr. Emergency Tel # : (800) 424-9300

HMIS Rating : * - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: * 1 *Flammability:* 0 *Reactivity:* 0

WHMIS Classes:



TOXIC

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS



VIVID FX

MSDS No.:6251, 6253, 6254, 6255, 6261

MSDS Preparation Date: January 3, 2007

Page 8 of 15

| Ingredients | CAS # | % (weight) | ACGIH TLV | | OSHA PEL | |
|--|------------|------------|--|--------------------|----------------|------|
| | | | TWA | STEL | PEL | STEL |
| Vivid FX Electric Green | | | | | | |
| Silica, crystalline-cristobalite | 14464-46-1 | 1.0 - 5.0 | 0.025 mg/m3 | N/Av | N/Av | N/Av |
| Formaldehyde | 50-00-0 | 0.1 - 1.0 | N/Av | N/Av | N/Av | N/Av |
| Vivid FX Hot Pink | | | | | | |
| Lead | 7439-92-1 | 0.1 - 1.0 | 0.05 mg/m3 | N/Av | 0.05 mg/m3 | N/Av |
| Arsenic | 7440-38-2 | 0.1 - 1.0 | 0.01 mg/m3 (As) | N/Av | 0.5 mg/m3 (As) | N/Av |
| Cadmium | 7440-43-9 | 0.1 - 1.0 | 0.01 mg/m3; 0.002 mg/m3 | N/Av | 0.1 mg/m3 | N/Av |
| Chromium | 7440-47-3 | 0.1 - 1.0 | 0.5 mg/m3 (Metal and Cr III compounds); 0.05 mg/m3 (Water-soluble Cr VI compounds); 0.01 mg/m3 (Insoluble CR VI compounds) | N/Av | 1 mg/m3 | N/Av |
| Vivid FX Lemon Yellow, Vivid FX Scarlet Red | | | | | | |
| Lead | 7439-92-1 | 0.1 - 1.0 | 0.05 mg/m3 | N/Av | 0.05 mg/m3 | N/Av |
| Mercury alkyl compounds | 7439-97-6 | 0.1 - 1.0 | 0.01 mg/m3 (alkyl); 0.1 mg/m3 (aryl); 0.025 mg/m3 (elemental and inorganic) | 0.03 mg/m3 (alkyl) | N/Av | N/Av |
| Arsenic | 7440-38-2 | 0.1 - 1.0 | 0.01 mg/m3 (As) | N/Av | 0.5 mg/m3 (As) | N/Av |
| Cadmium | 7440-43-9 | 0.1 - 1.0 | 0.01 mg/m3; 0.002 mg/m3 | N/Av | 0.1 mg/m3 | N/Av |
| Chromium | 7440-47-3 | 0.1 - 1.0 | 0.5 mg/m3 (Metal and Cr III compounds); 0.05 mg/m3 (Water-soluble Cr VI compounds); 0.01 mg/m3 (Insoluble CR VI compounds) | N/Av | 1 mg/m3 | N/Av |
| Vivid FX Orange | | | | | | |



VIVID FX

MSDS No.:6251, 6253, 6254, 6255, 6261

MSDS Preparation Date: January 3, 2007

Page 9 of 15

| | | | | | | |
|----------|-----------|-----------|--|------|---------|------|
| Chromium | 7440-47-3 | 1.0 - 5.0 | 0.5 mg/m3 (Metal and Cr III compounds); 0.05 mg/m3 (Water- soluble Cr VI compounds); 0.01 mg/m3 (Insoluble CR VI compounds) | N/Av | 1 mg/m3 | N/Av |
|----------|-----------|-----------|--|------|---------|------|

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Liquid in multiple colors. No.6251, 6254,6255: Warning. Contains lead. Harmful if inhaled or swallowed Irritating to eyes, respiratory system and skin. Contains material which can cause cancer. Contains material which can cause damage to the blood system, the liver and the kidneys. Contains material which may be a teratogen.

POTENTIAL HEALTH EFFECTS

Target organs : No.6261:Contains material which can cause damage to the blood system, the liver and the kidneys.

No. 6251, 6254, 6255: Eyes, skin, respiratory system, central nervous system, blood system, liver, brain and kidneys.

Routes of exposure : *Inhalation:* YES *Skin Absorption:* YES *Skin & Eyes:*YES *Ingestion:* YES

Potential acute health effects :

Eyes: Causes eye irritation. Prolonged or repeated exposure may be harmful to health. May cause conjunctivitis, irritation, and inflammation of mucous membranes. May cause burning sensation, redness and tearing (watering). Possible severe irritation.

Skin: Irritating to skin. Prolonged or repeated exposure may be harmful to health. Possible irritation, defatting or dermatitis (rash). Components of the product may be absorbed into the body through the skin. May cause central nervous system depression.

Inhalation: Can cause irritation of the respiratory tract. Prolonged exposure to vapors may be harmful to health. If higher concentrations are inhaled, additional symptoms may include coughing, shortness of breath, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. May cause mucous membrane irritation. Other adverse effects : Asphyxia. Severe lung irritation or lung damage, loss of appetite. Sanding and grinding dusts may be harmful if inhaled. Contains particles which may cause lung damage if inhaled in large quantities.

Ingestion: Lung aspiration hazard. This product may be aspirated (inhaled) into the lungs during ingestion. May cause lung inflammation. May cause mucous membrane irritation. Ingestion may cause symptoms similar to inhalation. May cause gastrointestinal irritation. Gastrointestinal irritation may include abdominal pain, nausea, diarrhea and vomiting. Other adverse effects : intoxication.

Potential chronic health effects

: Prolonged skin contact may defat the skin and produce dermatitis. Harmful by skin absorption. May cause central nervous system depression. Prolonged inhalation of vapors may cause lung damage, including chronic bronchitis. No. 6261: Contains crystalline silica; prolonged exposure by inhalation of particles can cause serious lung damage, including silicosis. Formaldehyde is a potential cancer hazard, a skin sensitizer and a respiratory sensitizer. Allergic respiratory reactions to these materials are characterized by asthma-like symptoms such as chest tightness, wheezing, shortness of breath and coughing.

No.6251, 6254, 6255: Overexposure to lead dust and fumes adversely affects blood and blood forming tissues, kidneys, liver and the central/peripheral nervous systems and male/female reproductive organs. Overexposure to lead may adversely affect nerve system, blood system, heart and eyes. May cause: Dermatitis, chronic bronchitis, tooth enamel erosion, and possible damage to the reproductive system, nervous system, kidneys, and liver.

Medical conditions aggravated by overexposure

: None expected, when used as intended.



VIVID FX

MSDS No.:6251, 6253, 6254, 6255, 6261

MSDS Preparation Date: January 3, 2007

Page 10 of 15

Additional health hazards : No.6261: Exposure to respirable silica is not possible under normal conditions of use. Crystalline Silica has been classified as a carcinogen in dry powder form only. Contains lead and lead compounds. Prolonged overexposure may result in lead toxicity syndrome which may result in permanent damage or death.

Potential environmental effects : None reported by the manufacturer.

SECTION 4 - FIRST AID MEASURES

Inhalation : If breathed in, move person into fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.

Skin contact : Flush with plenty of water. Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If irritation persists, seek prompt medical attention.

Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If irritation persists, seek prompt medical attention.

Ingestion : Call a physician or Poison Control Centre immediately. Do NOT induce vomiting. Guard against aspiration into lungs by having the individual turn on their left side.

Notes For Physician : Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

: Not flammable under normal conditions of handling. This product will not burn, due to its water content.

Flammability classification (OSHA 29 CFR 1910.1200)

: OSHA Combustible Liquid IIIB.

Flash point : Not applicable.

Flash point Method : Not applicable.

Auto-ignition temperature : Not available.

Lower flammable limit (% by vol.)

: Not applicable.

Upper flammable limit (% by vol.)

: Not applicable.

Suitable extinguishing media

: Dry chemical, foam, carbon dioxide and water fog.

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

Special fire-fighting procedures/equipment

: Firefighters should wear an approved full-face, self-contained breathing apparatus (SCBA) and impervious clothing. Water may be ineffective on fire, but may be helpful in cooling unburned containers. Do not use a solid water stream as it may scatter and spread fire. If water is used, fog nozzles are preferable.

Hazardous combustion products

: Oxides of carbon, nitrogen, and sulphur. Oxygen. Acrid fumes, toxic gases, oxides of metals.

Oxidizing properties

: None reported by the manufacturer.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Avoid breathing vapors. Wear resistant clothing and boots.

Environmental precautions : Prevent product from entering drains, sewers, waterways and soil.

Spill response/cleanup : Eliminate all ignition sources if safe to do so. Ventilate area of release. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13).

Containment : Should not be released into the environment. Recover free liquid or cover with inert absorbent material and place into appropriate container for disposal.



VIVID FX

MSDS No.:6251, 6253, 6254, 6255, 6261

MSDS Preparation Date: January 3, 2007

Page 11 of 15

SECTION 7 - HANDLING AND STORAGE

- Safe Handling procedures** : Use with adequate ventilation. Avoid breathing vapor or mist. Avoid contact with skin and eyes. Wash hands thoroughly after using this product, and before eating, drinking or smoking. Avoid breathing of dust created by cutting, sanding, or grinding. Sanding and grinding dusts may be harmful if inhaled. Do not re-use empty containers. Do not puncture container. Keep in properly labeled containers. Wear suitable protective equipment. Do not ingest. Keep out of direct sunlight.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Do not freeze. Keep container tightly closed when not in use. Store in upright position only. Keep out of the reach of children. Empty product containers may contain hazardous product residue. Store out of direct sunlight. Do not store near acids or acid-based products. Do not store in metal containers. When metal sprayers are used, they should be thoroughly cleaned immediately after use, including nozzles and accessories. Avoid use of metal buckets or paint containers when possible.
- Incompatible materials** : Oxidizing agents. Acids and bases. Aluminum. Ammonium salts. Other: magnesium, chlorinated rubber.
- Special packaging materials** : Liquid-proof glass, plastic or non-corrodible metal containers are recommended.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Ventilation and engineering measures** : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Use explosion-proof equipment. Discharge exhaust only in area away from ignition sources.
- Respiratory protection** : Use NIOSH/MSHA approved full-face respirator with an organic vapor cartridge if the recommended exposure limit is exceeded. In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.
- Skin protection** : Gloves impervious to the material are recommended.
- Eye / face protection** : Safety glasses with side-shields or chemical splash goggles.
- Other protective equipment** : Emergency showers and eyewash facilities should be nearby. Depending on conditions of use, safety shoes and additional protective clothing may also be necessary.
- General hygiene considerations** : Wash hands thoroughly after using this product, and before eating, drinking or smoking. Wash hands before breaks and at the end of workday.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|--|---|---|-------------------------------|
| Physical state | : Liquid. | Appearance | : Multiple colors. |
| Odor | : Not available. | Odor threshold | : Not available. |
| pH | : Not available. | | |
| Boiling point | : 100 °C -19.39 - 100 °C (No.6261) | Specific gravity | : 1.1 |
| Melting/Freezing point | : Not available. | Coefficient of water/oil distribution | : Not available. |
| Vapor pressure (mmHg @ 20° C / 68° F) | : 0.6 -29.3 (No.6251, 6254,6253) 0.6 (No. 6255, 6261) | Solubility in water | : Soluble |
| Vapor density (Air = 1) | : Heavier than air. | Evaporation rate (n-Butyl acetate = 1) | : Slower than n-butyl acetate |



VIVID FX

MSDS No.:6251, 6253, 6254, 6255, 6261

MSDS Preparation Date: January 3, 2007

Page 12 of 15

Volatile organic Compounds (VOC's) (lbs/gal;g/l) : 0.45 / 54.07 (No.6251)
 0.45 / 55.00 (No.6254)
 0.41 / 49.51 (No.6253)
 0.45 / 53.83 (No.6255)
 0.45 / 54.57 (No.6261)

Volatiles (% by weight) : 71.96 (No.6251, 6254,6255, 6261)
 54.4 (No.6253)

Viscosity : Not available.

Special Remarks On Fire Hazards

: Not flammable under normal conditions of use. This product will not burn, due to its water content. May spatter if the temperature exceeds the boiling point. Vapors may irritate eyes. May irritate skin.

SECTION 10 - REACTIVITY AND STABILITY DATA

Stability and reactivity : Stable under normal conditions.

Hazardous polymerization : Will not occur.

Conditions to avoid : High temperatures. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Oxidizing agents. Do not freeze.

Materials To Avoid And Incompatibility
 : See Section 7 (Handling and Storage) section for further details.

Hazardous decomposition products
 : See hazardous combustion products.

SECTION 11 - TOXICOLOGICAL INFORMATION

| <u>Ingredients</u> | <u>LC₅₀(4hr)</u> <u>inh, rat</u> | <u>LD₅₀</u> | |
|--|---|------------------------------------|--------------------|
| | | <u>oral</u> | <u>dermal</u> |
| Vivid FX Electric Green | | | |
| Silica, crystalline-cristobalite | N/Av | N/Av | N/Av |
| Formaldehyde | 308 mg/m ³ /2H (rat), 250 ppm/2H (rat) | 100 mg/kg (rat) | 300 mg/kg (rabbit) |
| Vivid FX Hot Pink | | | |
| Lead | N/Av | N/Av | N/Av |
| Arsenic | N/Av | 145 mg/kg (mouse); 763 mg/kg (rat) | N/Av |
| Cadmium | 28.4 mg/m ³ /4 hr (rat) | 2300 mg/kg (rat) | N/Av |
| Chromium | N/Av | N/Av | N/Av |
| Vivid FX Lemon Yellow, Vivid FX Scarlet Red | | | |
| Lead | N/Av | N/Av | N/Av |
| Mercury alkyl compounds | 19.1 mg/m ³ /4H (rat) | N/Av | N/Av |
| Arsenic | N/Av | 145 mg/kg (mouse); 763 mg/kg (rat) | N/Av |
| Cadmium | 28.4 mg/m ³ (rat) | 2330 mg/kg (rat) | N/Av |
| Chromium | N/Av | N/Av | N/Av |
| Vivid FX Orange | | | |
| Chromium | N/Av | N/Av | N/Av |

Toxicological data : Contains lead and lead compounds. Prolonged overexposure may result in lead toxicity syndrome which may result in permanent damage or death.



VIVID FX

MSDS No.:6251, 6253, 6254, 6255, 6261

MSDS Preparation Date: January 3, 2007

Page 13 of 15

- Carcinogenic status** : No.6261:Contains crystalline silica. Crystalline silica is classified as carcinogenic by IARC (Group 1), the ACGIH (Category A2) and the NTP (Group 1 - Known human carcinogen). Contains crystalline silica; prolonged exposure by inhalation of particles can cause serious lung damage, including silicosis. Crystalline Silica has been classified as a carcinogen in dry powder form only.
Contains the following chemical(s) listed as an Anticipated Carcinogen by NTP: Formaldehyde.
Contains the following chemical(s) listed as Group I (Human Carcinogens) by IARC: Formaldehyde.
Contains the following chemical(s) classified as ACGIH Group A2 (suspected human carcinogen): Formaldehyde.
- No.6251, 6254, 6255: Contains the following chemical rated as Group 2B by IARC: Lead
Contains the following chemicals listed as confirmed animal carcinogens (A3) by ACGIH: Lead .
Contains the following chemical(s) listed as an Anticipated Carcinogen by NTP: Lead.
Contains the following chemical classified as ACGIH Group A1 (confirmed human carcinogen): Arsenic.
Contains the following chemical(s) listed as Group I (Human Carcinogens) by IARC: Arsenic, Cadmium.
Contains the following chemical(s) listed as Known Carcinogen by NTP: Arsenic, Cadmium.
Contains the following chemical(s) classified as ACGIH Group A2 (suspected human carcinogen): Cadmium.
- Reproductive effects** : No.6255:Contains a chemical or chemicals which may cause male and/or female reproductive toxicity. This product contains: Lead, Cadmium.
No.6251, 6254: Contains a chemical or chemicals which may cause male and/or female reproductive toxicity. This product contains: Lead, Mercury, Cadmium.
- Teratogenicity** : No. 6251, 6254: Contains a chemical or chemicals which may be teratogenic. This product contains: Lead, Mercury, Arsenic.
No.6255: Contains a chemical or chemicals which may be teratogenic. This product contains: Lead, Arsenic.
- Mutagenicity** : No.6255:Contains a chemical or chemicals that may be mutagens. This product contains: Lead, cadmium.
No.6251, 6254: Contains a chemical or chemicals that may be mutagens. This product contains: Lead, Mercury, cadmium.
- Reproductive Effects** : No.6255:Contains a chemical or chemicals which may cause male and/or female reproductive toxicity. This product contains: Lead, Cadmium.
No.6251, 6254: Contains a chemical or chemicals which may cause male and/or female reproductive toxicity. This product contains: Lead, Mercury, Cadmium.
- Irritancy** : Eyes, skin, respiratory system and digestive system.
- Sensitization to material** : Formaldehyde is a potential cancer hazard, a skin sensitizer and a respiratory sensitizer. (No.6261)
Contains a chemical or chemicals which may cause skin sensitization. This product contains: Mercury (No.6251, 6254, 6255), chromium (No.6251, 6254, 6253, 6255).
- Synergistic materials** : None reported by the manufacturer.

SECTION 12 - ECOLOGICAL INFORMATION

- Environmental effects** : None known or reported by the manufacturer.
- Important environmental characteristics** : None known or reported by the manufacturer.
- Ecotoxicological** : No data is available on the product itself.

SECTION 13 - DISPOSAL CONSIDERATIONS

- Handling for Disposal** : See Section 7 (Handling and Storage) section for further details.
- Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules. Do not puncture or incinerate. Contact waste disposal services.



VIVID FX

MSDS No.:6251, 6253, 6254, 6255, 6261

MSDS Preparation Date: January 3, 2007

Page 14 of 15

SECTION 14 - TRANSPORTATION INFORMATION

| Regulatory Information | UN Number | Shipping Name | Class | Packing Group | Label |
|---|-----------|----------------|---------------|---------------|-------|
| TDG | None | Not regulated. | Not regulated | -None- | |
| TDG Additional information | None. | | | | |
| 49CFR/DOT | None | Not regulated. | Not regulated | -None- | |
| 49CFR/DOT Additional information | None. | | | | |
| ICAO/IATA | None | Not regulated. | Not regulated | -None- | |
| ICAO/IATA Additional information | None. | | | | |
| IMDG | None | Not regulated. | Not regulated | -None- | |
| IMDG Additional information | None. | | | | |

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

All ingredients are listed on the TSCA Inventory, or are exempted materials.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements, since it contains Toxic Chemical constituents above their de minimus concentrations. This product contains: Formaldehyde (No.6261); Lead, Arsenic, Cadmium (No.6251, 6254, 6255).

US State Right to Know Laws:

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and/or reproductive harm. This product contains: Formaldehyde; Silica, crystalline-Cristobalite (No.6261); Lead, Mercury, Arsenic, Cadmium, chromium (No.6251, 6254); Lead, Arsenic, Cadmium, chromium (No.6255); chromium (No. 6253) .

Canadian Regulations:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian WHMIS Classification: D2B (No.6253); D2A, D2B (No.6261, 6251, 6254, 6255).

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16 - OTHER INFORMATION



VIVID FX

MSDS No.:6251, 6253, 6254, 6255, 6261

MSDS Preparation Date: January 3, 2007

Page 15 of 15

- Legend**
- : ACGIH: American Conference of Governmental Industrial Hygienists
 - : IARC: International Agency for Research on Cancer
 - : N/Ap: not applicable
 - : N/Av: not available
 - : NIOSH: National Institute of Occupational Safety and Health
 - : NTP: National Toxicology Program
 - : OSHA: Occupational Safety and Health Administration

- References**
- : Information obtained from sources including original supplier's Material Safety Data Sheet, and references including RTECS and CCOHS Cheminfo.

| | |
|---|--|
| <p>Prepared for: Rosco Laboratories Inc. 52 Harbor View Avenue Stamford, CT, USA, 06902 Phone: (203) 708 8900 http://http://www.rosco.com/</p> |  |
| <p>Prepared by: ICC The Compliance Center Inc. Canada: 1-888-977-4834 USA: 1-888-442-9628 http://www.thecompliancecenter.com</p> |  |

DISCLAIMER OF LIABILITY

Every effort has been made to ensure that the safety information on this sheet is accurate, but because Rosco Laboratories, Inc. has no control over the conditions under which the product will be used, liability is limited exclusively to replacement or refund of the purchase price of this product. Except as stated herein, there are no express or implied warranties, including implied warranties of merchantability or fitness for a particular purpose. Rosco Laboratories, Inc. assumes no liability for injury or incidental or consequential damages arising out of storage, handling or use of this product.

Preparation Date: January 3, 2007

END OF DOCUMENT